C14 / C24

45×195 Pressure impregnated pine NTR CONSTRUCTION TIMBER C24

Wood species: Pine. Thickness: 45 mm.

PRESSURE-TREATED PINE | BOIS | EXTÉRIEUR



IDENTIFICATION

Dartank reference	**D7W115**
Dartank EAN	**3701839311202**
Material	**Pressure-treated pine**
Thickness	**45 mm**
Sales unit	**Linear metre**

OVERVIEW

Wood species: Pine. Thickness: 45 mm. Width: 195mm. Length: on request. Resistance class: C24. Profile: S4S. Protection method: NTR pressure impregnation. Price for: 1 gross linear m.

PRODUCT CHARACTERISTICS

Material	**Bois**
Wood species	**Pin**
Width	**20.0 cm**
Profile	**S4S**
Application	**Extérieur**
Length	**sur demande**
Protection	**Imprégnation sous pression NTR**
Strength class	**C24**

THE MATERIAL

Pressure-treated pine

Pressure-impregnated pine for outdoor use.

PERFORMANCE AND TEST RESULTS

Property	Standard	Result
Surface protection		**Pressure impregnation**

INSTALLATION

Installation

1. **Substructure** Install above ground with sufficient ventilation.
2. **Gap between boards** Leave about 4–7 mm between boards (more for the most reactive species).
3. **End gap** Allow about 2–3 mm between board ends.
4. **Screwing** Screws twice as long as the board is thick, driven at 90°, head flush (neither proud nor sunk).
5. **Pre-drilling** Always pre-drill, even with self-drilling decking screws.
6. **Pre-installation check** Starting installation means accepting the product's condition: report any defect before cutting, drilling or treating.
7. **Workmanship** Installation should be carried out by a professional in line with good building practice.

Storage

- **Stacking** Stack boards flat, strapped and/or evenly weighted, allowing air to circulate.
- **Shelter** Store in a dry place protected from water and UV.
- **Stacking** Unsecured storage risks cupping and twisting.

QUANTITIES

COVERAGE PER LINEAR METER — 5% cutting waste

LENGTH	BILLED	BARS
2 ml	2.1 ml	2
6 ml	6.3 ml	4
12 ml	12.6 ml	7
24 ml	25.2 ml	13

WARNINGS

- **Natural material** 100% natural, hygroscopic wood: it swells in wet weather and shrinks in hot weather. Grain and colour vary from board to board.
- **Dimensions** Actual width and thickness may differ by about 10% from the invoiced dimensions.
- **Natural material** Outdoors, weathering, deformation, cracking and dimensional change are natural for wood and are not grounds for a claim.

Non-contractual document. Values are given for guidance; official documents are available on request.