DECORATIVE WALL MOULDINGS

Mounting adhesive D14ML38 - Box of 7500 g (30 pieces)

Material: Polyurethane.

MOULDING MOUNTING ADHESIVE | POLYURÉTHANE



IDENTIFICATION

Dartank reference	**D14ML38**
Dartank EAN	**3701839355633**
Material	**Moulding mounting adhesive**
Packaging	**Carton de 7500 g (30 pièces)**
Sales unit	**Carton**

OVERVIEW

Material: Polyurethane. Packaging: Box of 7500 g (30 pieces).

PRODUCT CHARACTERISTICS

Material	**Polyuréthane**

THE MATERIAL

Moulding mounting adhesive

Mounting adhesive for fixing all types of mouldings to walls and ceilings; reinforced version for difficult substrates.

Application	**Interior**
Compatible paints	**Solvent-free water-based paint**
Field of use	**Bonding all types of mouldings to walls and ceilings; reinforced version for difficult substrates**

INSTALLATION

Installation

1. **Substrate** The substrate must be dry, clean, dust-free and degreased. A crumbling wall must be primed first.
2. **1. Measure and cut** Measure carefully, then cut in a mitre box with a fine-toothed saw (45° to 90° cuts). Allow about 10 % extra length for cuts.
3. **2. Sand and dry-fit** Deburr the cuts with fine sandpaper, then dry-fit the pieces to check wall contact and mitre alignment.
4. **3. Apply adhesive** Apply mounting adhesive over the whole contact surface. Also bond the joints between pieces, with jointing adhesive where the range provides one (gap of at least 1 mm).
5. **4. Press and clean** Press the piece along its full length; it can be adjusted for a few minutes. Remove excess adhesive with a spatula or damp sponge.
6. **5. Joints** Let joints dry for 24 h. Fill the wall/moulding junction with adhesive or filler, then sand. Do not use silicone sealant: it cannot be sanded or painted.
7. **6. Paint** Paint with a solvent-free water-based paint in two coats, following the paint maker's drying times. In bathrooms, choose a water-based paint suited to wet rooms.

MAINTENANCE

Care and maintenance

Routine	**No special maintenance. Dust with a broom or a vacuum cleaner fitted with a clean soft brush.**
Lacquered surfaces	**Versions with a factory lacquer finish can be cleaned with a damp cloth, water or an alcohol-free cleaner.**

> **WARNING**
>
> Solvent-based paints are prohibited: use a water-based paint. Do not use silicone sealant at junctions.

Non-contractual document. Values are given for guidance; official documents are available on request.