DARTANK

PRODUCT DATA SHEET



WALLPAPERS

Wallpaper Happy Cats Beige

Happy Cats Beige — custom wallpaper, animal motif.

Dartank reference **D5PP1150**

CHILDREN'S WALLPAPER

Wallpaper Happy Cats Beige

Happy Cats Beige — custom wallpaper, animal motif.

MADE-TO-MEASURE PRINTED CHILDREN'S WALLPAPER, CANVAS-EFFECT VINYL | COTON

INTÉRIEUR | COLLAGE

IDENTIFICATION

Dartank reference	**D5PP1150**
Dartank EAN	**3701839322451**
Material	**Made-to-measure printed children's wallpaper, canvas-effect vinyl**
Sales unit	**Square metre (m²)**

OVERVIEW

Overview

Children's room wallpaper printed to order on a fine canvas-texture vinyl chosen for the kids' collections. The substrate complies with European standard EN 12149 and is hung with the paste-the-wall method.

KEY BENEFITS

01
Designed for children
Substrate chosen specifically for children's room collections.

02
EN 12149 compliant
European safety standard for wallcoverings.

03
Soft canvas texture
Fine fabric-inspired texture for a cosy feel.

04
Made to measure
Design adjustable from 90 × 45 cm to 10 × 6 m.

05
Paste-the-wall
The dry strip is hung butt-jointed onto the pasted wall.

06
1:1 sample
Full-size fragment of the design, on the chosen substrate.

PRODUCT CHARACTERISTICS

Material	**Coton**
Application	**Intérieur**
Installation	**collage**

THE MATERIAL

Made-to-measure printed children's wallpaper, canvas-effect vinyl

Children's room design printed to order on canvas-texture vinyl, compliant with EN 12149.

Composition	**Vinyl with a canvas-texture coating**
Intended use	**Interior**
Backing	**Non-woven**
Application temperature	**18–25 °C**
Production format	**500 × 300 cm design, adjustable from 90 × 45 cm to 1000 × 600 cm**
Pasting method	**Paste the wall only, strip hung dry**
Strip joining	**Butt-jointed, no gap between strips**
Full adhesive drying time	**24 h**
Drying of new plaster or paint	**3 semaines ≈**

PERFORMANCE AND TEST RESULTS

Property	Standard	Result
Compliance / labels	EN 12149	**Compliant with EN 12149 (wallcoverings: migration of heavy metals, vinyl chloride monomer, formaldehyde)**

INSTALLATION

SUBSTRATE

Dry, clean, degreased, smooth wall of a light, uniform colour; old wallpaper and flaking paint fully removed, holes and cracks filled with plaster, glossy surfaces sanded.

PRIMER

Apply a deep-penetrating primer, preferably fungicidal, in two coats at least 24 h before hanging.

NEW PLASTER AND PAINT

Allow about 3 weeks to dry before hanging.

ROOM CONDITIONS

18 to 25 °C, no draughts, air conditioning, auxiliary heaters or sudden temperature changes, during installation and for at least 24 h afterwards.

SITE

Hang last, in a clean room: sockets removed, radiators taken down, holes drilled, acrylic sealing of skirtings and joinery done and adjacent walls painted beforehand.

Installation

1. **1. Check** Unroll all strips side by side and check pattern, shade, dimensions and condition; report any discrepancy before installing.
2. **2. Marking out** Draw a plumb line with a spirit or laser level, one strip width from the starting point, and mark the position of each strip.
3. **3. Pasting the wall** Apply adhesive to the wall with a roller or brush in a thin, even coat slightly wider than the strip; very thin at the edges to avoid squeeze-out. Never paste the strip.
4. **4. Hanging** Apply the dry strip from the top against the plumb line, then smooth it with a roller or soft brush from the centre outwards to remove air.
5. **5. Next strips** Hang the following strips, matching the pattern carefully; never place a joint in a corner or on an edge.
6. **6. Cleaning** Wipe off any adhesive immediately with a clean, slightly damp sponge or cloth; never let adhesive dry on the decorative face.
7. **7. Trimming** Trim the excess at top and bottom with a sharp utility knife guided by a metal spatula.
8. **8. Repositioning** Never slide a strip once stuck: if misplaced, peel it off and hang it again.

QUANTITIES

COVERAGE PER M² — 8% cutting waste

AREA	BILLED
5 m²	5.4 m²
10 m²	10.8 m²
20 m²	21.6 m²
50 m²	54 m²

PRECAUTIONS

- **Damp substrate** Never hang on a damp wall: loss of adhesion and risk of mould.
- **Drying too fast** Heat, draughts or auxiliary heaters can open the joints between strips.
- **Claims** Installed wallpaper can no longer be claimed: check all strips before hanging.

Non-contractual document. Values are given for guidance; official documents are available on request.