PAINTS & ADHESIVES

Window sill repair paste 1 kg

Window sill repair paste 1 kg

PRIMERS AND FILLING COMPOUNDS



IDENTIFICATION

Dartank reference	**D8PN21**
Dartank EAN	**3701839303733**
Material	**Primers and filling compounds**
Sales unit	**Piece**

OVERVIEW

Overview

Preparation and filling products: the joint primer binds dust and improves adhesion of the repair compound; the compound fills joints and corners before painting.

KEY BENEFITS

01
Adhesion
Primer improves compound adhesion in joints.

02
Invisible joints
Compound fills joints and corners before painting.

03
Sandable
Sanded after drying for a seamless surface.

04
Repair
Compounds dedicated to repairing sills and stucco.

05
Water-based
Tools clean up with water.

06
Pack sizes
Several sizes depending on the job.

THE MATERIAL

Primers and filling compounds

Joint primers, repair compounds and coating compound for finishing facade elements.

Composition	**Covering compound: acrylic-styrene copolymer, quartz fillers**

INSTALLATION

Storage

- **Primer and repair compound** Between +5 °C and +30 °C, 6 months in the sealed original packaging.
- **Covering compound** Between +5 °C and +25 °C in closed packaging, use within 12 months; protect from frost.

> **WARNING**
>
> - **Manufacturer's sheet** Follow the technical data sheet, safety data sheet and packaging instructions.

Non-contractual document. Values are given for guidance; official documents are available on request.