SCANDINAVIAN PINE

# Pressure-impregnated Brown Pine Ribbed Panel 28×120 class C

Wood species: Pine. Thickness: 28 mm.

PRESSURE-TREATED PINE | BOIS | EXTÉRIEUR | BC




## IDENTIFICATION

| | |
|---|---|
| Dartank reference | **D7W112P** |
| Dartank EAN | **3701839311233** |
| Material | **Pressure-treated pine** |
| Thickness | **28 mm** |
| Sales unit | **Square metre (m²)** |

## OVERVIEW

Wood species: Pine. Thickness: 28 mm. Width: 120mm. Length: on request. Class: BC. Profile: Ryflowany/Gładki. Protection method: Brown pressure impregnation. Price for: 1 m² gross.

## PRODUCT CHARACTERISTICS

| | |
|---|---|
| Material | **Bois** |
| Wood species | **Pin** |
| Width | **120 mm** |
| Profile | **Rainuré/Lisse** |
| Class | **BC** |
| Application | **Extérieur** |
| Length | **sur demande** |
| Protection | **Imprégnation sous pression Brun** |

## THE MATERIAL

### Pressure-treated pine

Pressure-impregnated pine for outdoor use.

## PERFORMANCE AND TEST RESULTS

| Property | Standard | Result |
|---|---|---|
| Surface protection | | **Pressure impregnation** |

## INSTALLATION

### Installation

1. **Substructure** Install above ground with sufficient ventilation.
2. **Gap between boards** Leave about 4–7 mm between boards (more for the most reactive species).
3. **End gap** Allow about 2–3 mm between board ends.
4. **Screwing** Screws twice as long as the board is thick, driven at 90°, head flush (neither proud nor sunk).
5. **Pre-drilling** Always pre-drill, even with self-drilling decking screws.
6. **Pre-installation check** Starting installation means accepting the product's condition: report any defect before cutting, drilling or treating.
7. **Workmanship** Installation should be carried out by a professional in line with good building practice.

### Storage

- **Stacking** Stack boards flat, strapped and/or evenly weighted, allowing air to circulate.
- **Shelter** Store in a dry place protected from water and UV.
- **Stacking** Unsecured storage risks cupping and twisting.

## QUANTITIES

### COVERAGE PER M² — 8% cutting waste

| AREA | BILLED |
|---|---|
| 5 m² | 5.4 m² |
| 10 m² | 10.8 m² |
| 20 m² | 21.6 m² |
| 50 m² | 54 m² |

## WARNINGS

- **Natural material** 100% natural, hygroscopic wood: it swells in wet weather and shrinks in hot weather. Grain and colour vary from board to board.
- **Dimensions** Actual width and thickness may differ by about 10% from the invoiced dimensions.
- **Natural material** Outdoors, weathering, deformation, cracking and dimensional change are natural for wood and are not grounds for a claim.

Non-contractual document. Values are given for guidance; official documents are available on request.