SKIRTING BOARDS

Skirting board – D4PL15T

Plinth D4PL15T is an MDF plinth, semi-matt lacquer finish.

LACQUERED MDF | MDF | INTÉRIEUR | COLLAGE



IDENTIFICATION

Dartank reference	**D4PL15T**
Dartank EAN	**3701839324240**
Material	**Lacquered MDF**
Colors	**Blanc**
Thickness	**1,6 cm**
Sales unit	**Piece**

OVERVIEW

Plinth D4PL15T is an MDF plinth, semi-matt lacquer finish. Characteristics: thickness 1.6 cm. Ideal indoors.

PRODUCT CHARACTERISTICS

Material	**MDF**
Finish	**Laque semi-mate**
Application	**Intérieur**
Installation	**collage**

THE MATERIAL

Lacquered MDF

Skirting boards in medium-density fibreboard (MDF), factory-lacquered in semi-matt white.

Application	**Interior**
Composition	**Medium-density fibreboard (MDF)**
Factory finish	**Factory semi-matt white lacquer**
Installation method	**Bonding**
Compatible paints	**Solvent-free water-based paint**

INSTALLATION

Installation

1. **Substrate** The substrate must be dry, clean, dust-free and degreased. A crumbling wall must be primed first.
2. **1. Measure and cut** Measure carefully, then cut in a mitre box with a fine-toothed saw (45° to 90° cuts). Allow about 10 % extra length for cuts.
3. **2. Sand and dry-fit** Deburr the cuts with fine sandpaper, then dry-fit the pieces to check wall contact and mitre alignment.
4. **3. Apply adhesive** Apply mounting adhesive over the whole contact surface. Also bond the joints between pieces, with jointing adhesive where the range provides one (gap of at least 1 mm).
5. **4. Press and clean** Press the piece along its full length; it can be adjusted for a few minutes. Remove excess adhesive with a spatula or damp sponge.
6. **5. Joints** Let joints dry for 24 h. Fill the wall/moulding junction with adhesive or filler, then sand. Do not use silicone sealant: it cannot be sanded or painted.
7. **6. Paint** Paint with a solvent-free water-based paint in two coats, following the paint maker's drying times. In bathrooms, choose a water-based paint suited to wet rooms.

MAINTENANCE

Care and maintenance

Routine	**No special maintenance. Dust with a broom or a vacuum cleaner fitted with a clean soft brush.**
Lacquered surfaces	**Versions with a factory lacquer finish can be cleaned with a damp cloth, water or an alcohol-free cleaner.**

COLOURS AND OPTIONS

Colors

- Blanc

> **WARNING**
>
> Solvent-based paints are prohibited: use a water-based paint. Do not use silicone sealant at junctions.

Non-contractual document. Values are given for guidance; official documents are available on request.