DOOR FRAMES

Plinth block for door casing 9 × 20 × 4 cm

Corbel for door casing

ACRYLIC COMPOUND



IDENTIFICATION

Dartank reference	**D8ML537A**
Dartank EAN	**3701839304808**
Material	**Acrylic compound**
Sales unit	**Piece**

OVERVIEW

Corbel for door casing

THE MATERIAL

Acrylic compound

Door-surround elements and reliefs cast in acrylic compound: pilasters, architrave plinth blocks and wall reliefs, ready to fit and paint.

Application	**Interior**
Composition	**Acrylic compound**
Factory finish	**Ready to paint**
Compatible paints	**Solvent-free water-based paint**

INSTALLATION

Installation

1. **Substrate** The substrate must be dry, clean, dust-free and degreased. A crumbling wall must be primed first.
2. **1. Measure and cut** Measure carefully, then cut in a mitre box with a fine-toothed saw (45° to 90° cuts). Allow about 10 % extra length for cuts.
3. **2. Sand and dry-fit** Deburr the cuts with fine sandpaper, then dry-fit the pieces to check wall contact and mitre alignment.
4. **3. Apply adhesive** Apply mounting adhesive over the whole contact surface. Also bond the joints between pieces, with jointing adhesive where the range provides one (gap of at least 1 mm).
5. **4. Press and clean** Press the piece along its full length; it can be adjusted for a few minutes. Remove excess adhesive with a spatula or damp sponge.
6. **5. Joints** Let joints dry for 24 h. Fill the wall/moulding junction with adhesive or filler, then sand. Do not use silicone sealant: it cannot be sanded or painted.
7. **6. Paint** Paint with a solvent-free water-based paint in two coats, following the paint maker's drying times. In bathrooms, choose a water-based paint suited to wet rooms.

MAINTENANCE

Care and maintenance

Routine	**No special maintenance. Dust with a broom or a vacuum cleaner fitted with a clean soft brush.**
Lacquered surfaces	**Versions with a factory lacquer finish can be cleaned with a damp cloth, water or an alcohol-free cleaner.**

QUANTITIES

VARIANTS — 7

VARIANT	REF.
Socle pour chambranle classique pour encadrement de porte	D8ML536A
Socle pour chambranle : élégance classique pour vos encadrements de porte	D8ML575A
Socle pour Chambranle 9 × 9 × 3,5 cm	D8ML540A
Socle pour Chambranle D8ML541A forme carrée pour vos Encadrements de Porte	D8ML541A
Socle pour chambranle : forme cubique pour vos encadrements de porte	D8ML542A
Socle pour chambranle : design minimaliste et géométrique pour vos encadrements de porte	D8ML543A
Socle pour chambranle en forme de cadre en relief pour vos encadrements de porte	D8ML544A

WARNING

Solvent-based paints are prohibited: use a water-based paint. Do not use silicone sealant at junctions.

Non-contractual document. Values are given for guidance; official documents are available on request.