FLOOR WITH OLD BRICK TILES

Brown old brick cement tiles – L: 13.5 cm x H: 27 cm x Th: 1.5 cm

Consumption for 1 m2, allowing for approx.

CEMENT BRICK-EFFECT PAVER FOR FLOORS AND TERRACES



IDENTIFICATION

Dartank reference	**D11SO13**
Dartank EAN	**3701839358665**
Material	**Cement brick-effect paver for floors and terraces**
Colors	**Brun**
Sales unit	**Piece**

OVERVIEW

Overview

The look of a century-old brick floor without the spalling of ordinary brick outdoors: cement tiles and pavers for terraces, paths, steps and sills.

KEY BENEFITS

01
Old brick look without outdoor spalling

02
Weather resistant

03
Two thicknesses: 1.5 cm for flush finishes, 3.5 cm for terraces and steps

04
Matching step, stair-nosing and sill pieces

05
Indoor and outdoor

06
Shades coordinated with the wall slips

THE MATERIAL

Cement brick-effect paver for floors and terraces

Cement floor tiles and pavers imitating old brick, 1.5 or 3.5 cm thick, with step, stair-nosing and window-sill elements.

Composition	**Moulded cement-based element**
Manufacturing	**Hand-crafted, hand-moulded**
Use	**Floors, terraces, outdoor and indoor stairs, window sills**
Thickness	**15–35 mm**
Nominal size	**Approx. 13.5 × 27 cm (tile); pavers 6.5 × 27 and 6.5 × 13.5 cm**
Weight per m²	**22 kg/m² env.**
Cutting	**Stone or concrete cutting disc, or score the face and snap for a more natural edge**
Coverage	**Approx. 23.5 tiles/m² with approx. 1.5 cm joint**
Joint width	**1.5 cm (floor)**
Grout consumption	**Approx. 3 kg/m² for a 1.5 cm joint**
Recommended cutting allowance	**3 % env.**

PERFORMANCE AND TEST RESULTS

Property	Standard	Result
Weather resistance		**Resists temperature changes, moisture, rain and UV (outdoor version)**

INSTALLATION

Installation

1. **Substrate** Dry, degreased, clean substrate free of loose parts, then primed.
2. **Movement joints** Repeat every wall movement joint with a joint in the cladding at the same place.
3. **Bonding** Choose the tile adhesive for the use: indoor or outdoor, wall or floor, fireplace wall, kitchen or bathroom.
4. **Cutting** Cut with a stone/concrete disc, or score the face and snap for a natural-looking edge.
5. **Grouting** Grout with a mortar matching the colour; one slip collection can be laid without joints.
6. **Impregnation** Impregnate after laying and grouting, once the grout has cured for at least 24 h; recommended outdoors, in kitchens, bathrooms, on fireplace walls and in hallways.

COLOURS AND OPTIONS

Colors

- Brun

> **WARNING**
>
> Hand-moulded product: each piece varies in relief and shade. Mix pieces from several boxes when laying.

Non-contractual document. Values are given for guidance; official documents are available on request.